



Customer: SR(SLOVENIA)
 Sales manager: Jonas Selsvik
 Date created: 02-07-10
 Latest revision: 06-02-27
 Approved: 06-02-27 by PE

Series production OK

General rig description

Conventional Fractional
 Deckstepped 2-spreader
 Untapered Sloop

Rig dimensions

Forestay height FH: 15 540 mm
 Main sail luff length P: 15 380 mm
 Boom height above deck BH: 1 360 mm
 Main sail foot length E: 4 700 mm
 Main boom sheet pos S: 2 700 mm
 Spinnaker pole length SPL: 4 590 mm

Chainplates dist. from cl mast

Lateral Long

Cap shrouds: 1320 430 mm (18,0°)
 Aft lowers: 1320 430 mm
 Deck above chainplates: 400 mm
 Deck above waterline: 1790 mm

Hull and righting moment

Length: 11 990 mm
 Beam: 4 120 mm
 Draft: 2 150 mm
 Displacement: 7 200 Kg
 Ballast: 2 450 Kg
 Conventional keel
 Equipped boat
 Heeling test RM: 43,7 kNm @30°

Spar sections

Mast: C245
 Boom: B171
 Spin. pole: S096

Furlex

Forestay: 208

Notes (2 lines)

Sheet sliders separated min 2x400mm, center block at S=2700 or B200 required.

